



# Product Description

## Architectural MSD

Architectural MSD – single ended night colours The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent colour rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

### Benefits

- High lumen output
- Low cost of ownership
- Excellent colours

### Features

- Long lifetime
- Compact arc
- Excellent colour characteristics
- Universal burning position

### Application

- Display lighting
- Architectural lighting
- Studio and disco lighting
- Fibre-optic lighting

### Warnings and Safety


- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

# Architectural MSD


## Versions



## Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 1200.1CT/3	42.5 mm	14.0 mm	84 mm	86 mm	85 mm	183 mm	54 mm	53 mm	52 mm



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSD 700.1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	54 mm	53 mm	52 mm

### General Information

Cap-Base	G22
Main Application	Studio/Disco
Operating Position	UNIVERSAL
System Description	na

### Light Technical

Colour Code	-
-------------	---

## Controls and Dimming

Order Code	Full Product Name	Dimmable
928170405114	MSD 700.1CT/3	Yes

## Architectural MSD

Order Code	Full Product Name	Dimmable
928172005114	MSD 1200.1CT/3	No

### Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928170405114	MSD 700.1CT/3	11 A	700 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
928172005114	MSD 1200.1CT/3	13.8 A	1200 W

### General Information

Order Code	Full Product Name	Life To 50% Failures (Nom)
928170405114	MSD 700.1CT/3	3000 h

Order Code	Full Product Name	Life To 50% Failures (Nom)
928172005114	MSD 1200.1CT/3	2000 h

### Light Technical

Order Code	Full Product Name	Correlated Colour			
		Temperature (Nom)	Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928170405114	MSD 700.1CT/3	5900 K	75	46800 lm	52000 lm

Order Code	Full Product Name	Correlated Colour			
		Temperature (Nom)	Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
928172005114	MSD 1200.1CT/3	6000 K	80	-	92000 lm

### Colour Rendering Diagrams

