



SmartBright Road

BRP132 LED140/WW 140W 220-240V DM GM MS

SmartBright Road - 14000 lm - 140 W - 3000 K

The SmartBright road is ideal for new streets and for renovating existing installations: this affordable range of lighting solutions combines clean, high-quality light with significant energy savings and reduced maintenance.

Product data

General Information	
Lamp colour code	730 warm white
Driver included	Yes
Optical cover/lens type	PC-MLO [Polycarbonate micro lens optic]
Control interface	-
Connection	CU3 [Connection unit 3-pole]
Cable	-
Protection class IEC	Safety class I (I)
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
Operating and Electrical	
Input Voltage	220/240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.9
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminium

Optical cover/lens material	Polycarbonate
Overall length	508.2 mm
Overall width	325.5 mm
Overall height	85 mm
Effective projected area	0.14 m ²
Colour	Dark Grey

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	14000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>70
Initial chromaticity	(0.43, 0.40) SDCM < 5
Initial input power	140 W
Power consumption tolerance	+/-10%

SmartBright Road

Application Conditions

Ambient temperature range -40 to +50 °C

Product Data

Full product code 911401655206
Order product name BRP132 LED140/WW 140W 220-240V DM GM MS
Order code 911401655206
Local order code BRP132140WWMOT

SAP numerator – quantity per pack 1


Numerator – packs per outer box 1

SAP material 911401655206

SAP net weight (piece) 3.999 kg



Dimensional drawing



BRP130/131/132 SmartBright Road

