



Medical Therapy Jaundice PL-L/PL-S

PL-L 18W/52/4P 1CT/25

By emitting light almost entirely within the 400 to 500 nm bandwidth these Medical Therapy Jaundice PL-L lamps have no radiation from the short wave UVB waveband. They are therefore ideal for treating new born babies suffering from hyperbilirubinemia (neonatal jaundice) and Crigler-Najjar Syndrome (CNS). Moreover, the bandwidth of these lamps peak at the most effective treatment wavelength of 450 nm. This highly efficacious phototherapy treatment has eliminated the need for blood transfusions in almost all jaundiced infants. In addition, with the compact format of this PL-L lamp equipment manufacturers have more design freedom in developing their solutions. By emitting a full spectrum of a high color temperature, the PL-L /953 lamps are ideal for treating SAD.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Chromaticity coordinate Y (nom.)		75	
Cap base	2G11 [2G11]				
Main application	-				
Life to 50% failures preheat (nom.)	8000 h				
Light Technical		Operating and Electrical			
Colour Code	52	Power (Rated) (Nom)	17.5 W		
Lamp Luminous Flux 25°C EL (Nom)	330 lm	Lamp current (nom.)	0.375 A		
Chromaticity coordinate X (nom.)	155	Voltage (Nom)	57 V		
		Mechanical and Housing			
		Cap-base information	4 Pins (4P)		

Medical Therapy Jaundice PL-L/PL-S

Bulb shape	2xT16
Approval and Application	
Mercury (Hg) content (nom.)	4.4 mg
Product Data	
Full product code	872790080517800
Order product name	PL-L 18W/52/4P 1CT/25
EAN/UPC – product	8727900805178

Order code	927904105206
Local order code	PLL18W524P
SAP numerator – quantity per pack	1
Numerator – packs per outer box	25
SAP material	927904105206
SAP net weight (piece)	60.900 g

Dimensional drawing



Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
PL-L 18W/52/4P 1CT/25	18 mm	39 mm	188.2 mm	214 mm	220.6 mm

PL-L 18W/52/4P 219mm

