



MASTER TL5 High Efficiency

MASTER TL5 HE 28W/830 SLV/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Chromaticity coordinate X (nom.)		0.44
Cap base	G5 [G5]	Chromaticity coordinate Y (nom.)		0.403
Life to 50% failures preheat (nom.)	24000 h	Colour Temperature, horizontal (Nom)		3000 K
Features	na [Not Applicable]	Lamp Luminous Efficacy EM (Nom)		96 lm/W
System description	High Efficiency	Colour Rendering Index,horiz (Max)		85
LSF preheat 2,000 hours rated	99 %	Colour Rendering Index,horiz (Min)		80
LSF preheat 4,000 hours rated	99 %	Colour Rendering Index,horiz (Nom)		82
LSF preheat 6,000 hours rated	99 %	LLMF 2000 h Rated		96 %
LSF preheat 8,000 hours rated	99 %	LLMF 4000 h Rated		95 %
LSF preheat 16,000 hours rated	97 %	LLMF 6000 h Rated		94 %
LSF preheat 20,000 hours rated	84 %	LLMF 8000 h Rated		93 %
	Sphere	LLMF 12000 h Rated		92 %
		LLMF 16000 h Rated		91 %
		LLMF 20000 h Rated		90 %
Light Technical		Operating and Electrical		
Colour Code	830 [CCT of 3,000 K]	Power (Rated) (Nom)	28.1 W	
Lamp Luminous Flux 25°C EL (Nom)	2675 lm	Lamp current (nom.)	0.170 A	
Lamp Luminous Flux (Nom)	2675 lm			
Colour Designation	Warm white (WW)			
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	104 lm/W			

MASTER TL5 High Efficiency

Temperature	
Design temperature (nom.)	35 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	Green Plate
Bulb shape	T5 [16 mm (T5)]
Approval and Application	
Energy Efficiency Class	F
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	29 kWh

	423460
Product Data	
Full product code	871150063946255
Order product name	MASTER TL5 HE 28W/830 SLV/40
EAN/UPC – product	8711500639462
Order code	927926583055
Local order code	TL528W830HE
SAP numerator – quantity per pack	1
Numerator – packs per outer box	40
SAP material	927926583055
SAP net weight (piece)	104.500 g
ILCOS code	FDH-28/30/1B-L/P-G5-16/1150



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 28W/830 SLV/40	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm

TL5 28W/830/GP HE

Photometric data



Lightcolour /830

Lightcolour /830

MASTER TL5 High Efficiency

Lifetime



LDLE_TL5-HE8_0001-Life expectancy diagram

LDLE_TL5-HE8_0002-Life expectancy diagram



LDLM_TL5-HE8_0001-Lumen maintenance diagram

