



SmartBright LED Oyster

CL261 DS Oyster 15.5W 30-40-65K IP54 ANZ

The new Philips tri-colour Splashproof Oyster offers exceptional value. It is perfect for everyday lighting installations. It comes with a three CCT selection switch to provide flexibility to the customer.


Product data

General Information		Colour	
Lamp colour code	3000/4000/6500	White	
Light source replaceable	No	Approval and Application	
Luminaire light beam spread	110°	Ingress protection code	IP54 [Dust accumulation-protected, splash-proof]
Protection class IEC	Safety class I (I)	Mech. impact protection code	IK03 [0.3 J]
Operating and Electrical		Initial Performance (IEC Compliant)	
Input Voltage	220 to 240 V	Initial luminous flux (system flux)	1400 lm
Input frequency	50 or 60 Hz	Initial LED luminaire efficacy	87.00 lm/W
Power factor (min.)	0.9	Lamp colour temperature	3000 4000 6500 K
Controls and Dimming		Colour Rendering Index	80
Dimmable	Yes	Initial input power	15.5 W
Mechanical and Housing		Over Time Performance (IEC Compliant)	
Housing material	Metal-Plastic	Median useful life L70B50	30000 h
Overall length	87 mm	Application Conditions	
Overall width	87 mm	Ambient temperature range	-20 to +40 °C
Overall height	88 mm	Product Data	
Overall diameter	300 mm	Full product code	871951426677300



SmartBright LED Oyster

Order product name	CL261 DS Oyster 15.5W 30-40-65K IP54 ANZ
EAN/UPC – product	8719514266773
Order code	929002562219
Local order code	CL261RD155WIP
SAP numerator – quantity per pack	1
Numerator – packs per outer box	5

SAP material	929002562219
SAP net weight (piece)	0.480 kg




Dimensional drawing



CeilingDip SW RD15.5W 27-40-65K HV AU/NZ


Photometric data




General Information 131 Page Lighting SV Page 1/1

Ceiling CL261 DS Oyster 15.5W IP54 ANZ

Lifetime



B50L70 30K 1



B50L70 30K 1

SmartBright LED Oyster

