



Halogen reflector

13186 90W GX5.3 14.5V 1CT/24

Quartz halogen lamps with integral reflector which serves as an efficient mirror condenser system

Product data

| General Information | |
|--------------------------------------|----------------|
| Cap base | GX5.3 [GX5.3] |
| Philips code | 13186 |
| ANSI Code | EPX-EPV |
| LIF Code | - |
| Burning Position | S105 [s105] |
| Main application | Projection |
| Life to 50% failures (nom.) | 500 h |
| J code | - |
| Light Technical | |
| Colour Temperature, horizontal (Nom) | 3200 K |
| Colour Rendering Index,horiz (Nom) | 100 |
| Operating and Electrical | |
| Power (Rated) (Nom) | 90 W |
| Voltage (Nom) | 14.5 V |
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Cap-base information | na [-] |

| Bulb material | Quartz-UV Open |
|-------------------------------|----------------|
| Reflector finish | - |
| Filament shape | - |
| Filament dimensions WxH | - |
| Bulb shape | R50 [R 50mm] |
| Luminaire Design Requirements | |
| Bulb temperature (max.) | 900 °C |
| Pinch temperature (max.) | 350 °C |
| Working distance WD | 155 mm |

| Product Data | |
|-----------------------------------|------------------------------|
| Full product code | 871869669015400 |
| Order product name | 13186 90W GX5.3 14.5V 1CT/24 |
| EAN/UPC – product | 8718696690154 |
| Order code | 923891214905 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 24 |
| SAP material | 923891214905 |
| SAP net weight (piece) | 26.000 g |

Halogen reflector

Dimensional drawing



13186 90W GX5.3 14.5V 1CT/24

| Product | D (max) | C (max) |
|------------------------------|---------|---------|
| 13186 90W GX5.3 14.5V 1CT/24 | 50 mm | 45 mm |

