



Product Description

Flexo Print

Tubular low-pressure mercury vapour discharge lamps

Benefits

- Best match with photo sensitizers
- Highest output on irradiated area

Features

- Internally coated with a white fluorescent powder to convert the short-wave UV radiation into useful actinic radiation
- Emit radiation in the range 380 - 480 nm with a maximum at 420 nm
- Spectral energy distribution in accordance with the spectral sensitivity of a number of diazo copying papers
- For maximum beauty of marine aquaria, TL /03 "Aqua Coral" lamps can be used in combination with full-spectrum "Natural Daylight" fluorescent lamps

Application

- Diazo copying machines
- Marine aquaria
- Phototherapy (neonatal jaundice treatment)

Warnings and Safety



- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Flexo Print

Versions



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL 60W/10-R SLV/25	40.5 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm
TL 80W/10-R SLV/25	40.5 mm	1500 mm	1507.1 mm	1504.7 mm	1514.2 mm
TL 100W/10-R UV-A	40.5 mm	1763.8 mm	1770.9 mm	1768.5 mm	1778 mm

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-K 40W UVA-1	40.5 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

General Information

Cap-Base G13

Light Technical

Colour Code 10-R

Colour Designation Ultra Violet A

Mechanical and Housing

Bulb Shape T38

UV

UV-B/UV-A (IEC) 0.1 %

Operating and Electrical

Order Code	Full Product Name	Lamp Current		Power (Rated)
		(Nom)	Voltage (Nom)	(Nom)
928004101029	TL-K 40W UVA-1	0.86 A	50 V	40.5 W
928005901029	TL 80W/10-R SLV/25	0.83 A	110 V	80 W

Order Code	Full Product Name	Lamp Current		Power (Rated)
		(Nom)	Voltage (Nom)	(Nom)
928006901029	TL 100W/10-R UV-A	0.97 A	122 V	100 W
928008401003	TL 60W/10-R SLV/25	0.7 A	102 V	62 W

General Information

Order Code	Full Product Name	Life To 50%	Useful Life	Main Application
		Failures (Nom)	(Nom)	
928004101029	TL-K 40W UVA-1	2000 h	2000 h	Reprography (R)
928005901029	TL 80W/10-R SLV/25	1000 h	1000 h	Reprography (R)

Order Code	Full Product Name	Life To 50%	Useful Life	Main Application
		Failures (Nom)	(Nom)	
928006901029	TL 100W/10-R UV-A	2000 h	1000 h	Phototherapy
928008401003	TL 60W/10-R SLV/25	2000 h	1000 h	Reprography (R)

UV

Order Code	Full Product Name	UV-A Radiation 100Hr	UV-A Radiation 0Hr
		(IEC)	(IEC)
928004101029	TL-K 40W UVA-1	7.4 W	8.0 W
928005901029	TL 80W/10-R SLV/25	20.5 W	-

Order Code	Full Product Name	UV-A Radiation 100Hr	UV-A Radiation 0Hr
		(IEC)	(IEC)
928006901029	TL 100W/10-R UV-A	26.0 W	28.0 W
928008401003	TL 60W/10-R SLV/25	15.8 W	-

Approval and Application

Order Code	Full Product Name	Mercury (Hg) Content (Nom)
928004101029	TL-K 40W UVA-1	-
928005901029	TL 80W/10-R SLV/25	13.0 mg

Order Code	Full Product Name	Mercury (Hg) Content (Nom)
928006901029	TL 100W/10-R UV-A	13.0 mg
928008401003	TL 60W/10-R SLV/25	13.0 mg

