



# GreenUp Highbay G2

## BY560P LED210/NW PSD/CL WB CAU

840 neutral white - Power supply unit with DALI interface - Wide beam

Height is not an issue any more, maximum 16 m movement detection together with the wireless ZigBee control, GreenUp HighBay G2, light up your space smartly.

### Warnings and Safety

- The product is IPX0 & as such is not protected against water ingress and as such we strongly recommend that the environment in which the luminaire is to be installed is suitably checked
- If the above advice is not taken and the luminaires are subject to water ingress, Philips/Signify cannot guarantee safe failure and product warranty will become void

### Product data

General Information			
Beam angle of light source	- °	Glow-wire test	650/5 [ Temperature 650 °C, duration 5 s]
Lamp colour code	840 neutral white	Flammability mark	F [ For mounting on normally flammable surfaces]
Light source replaceable	No	CE mark	CE mark
Number of gear units	1 unit	ENEC mark	-
Driver/power unit/transformer	PSD [ Power supply unit with DALI interface]	Warranty period	3 years
Driver included	Yes	Constant light output	No
Optic type	WB [ Wide beam]	Number of products on MCB (16 A type B)	24
Optical cover/lens type	LIN-PC [ Linear-lens array in polycarbonate cover]	LED engine type	LED
Luminaire light beam spread	90°	<b>Operating and Electrical</b>	
Control interface	DALI	Input Voltage	220 to 240 V
Connection	No [ -]	Input frequency	50 to 60 Hz
Cable	Cable 3.0 m with plug	Inrush current	5.1 A
Protection class IEC	Safety class I (I)	Inrush time	760 ms

# GreenUp Highbay G2

Power factor (min.)	0.95
---------------------	------

## Controls and Dimming

Dimmable	Yes
----------	-----

## Mechanical and Housing

Housing material	Aluminum extruded
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Clear
Overall length	525 mm
Overall width	280 mm
Colour	Aluminium and White

## Approval and Application

Ingress protection code	IP40 [ Wire-protected]
Mech. impact protection code	IK03 [ 0.3 J]

## Initial Performance (IEC Compliant)

Initial luminous flux	21000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	137 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80

Initial chromaticity	(0.38.0.38)SDCM<5
Initial input power	153 W
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)


Median useful life L70B50	65000 h
Median useful life L80B50	45000 h
Median useful life L90B50	25000 h

## Application Conditions


Ambient temperature range	-20 to +45 °C
Maximum dimming level	1% (depends on dimmer, ELV)
Suitable for random switching	No

## Product Data

Full product code	871016333692300
Order product name	BY560P LED210/NW PSD/CL WB CAU
EAN/UPC – product	8710163336923
Order code	911401505651
Numerator – quantity per pack	1
SAP numerator – packs per outer box	2
Material no. (12 NC)	911401505651
SAP net weight (piece)	3.450 kg



## Dimensional drawing



GreenUp High-bay BY550P/BY550X

## GreenUp Highbay G2

