



GreenPerform Highbay Rectangular

BY570P LED200/840 PSU WB CAU CL

Transparent dome

As the first IP65 rectangular LED highbay under the GreenPerform family, the GreenPerform Highbay Rectangular with dedicated optical design, leading system efficiency and compact dimension, is the optimised solution for warehousing and logistics-related applications.

Product data

General Information	
Lamp colour code	840 neutral white
Optical cover/lens type	TSDM [Transparent dome]
Control interface	-
Protection class IEC	Safety class I (I)
CE mark	-
Number of products on MCB (16 A type B)	6
LED engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.95
Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Aluminum die-cast
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Clear
Overall length	27 mm
Overall width	11 mm
Overall height	34 mm
Colour	Grey

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial Performance (IEC Compliant)	
Initial luminous flux	20000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	139 lm/W
Lamp colour temperature	4000 K

GreenPerform Highbay Rectangular

Colour Rendering Index	>80
Initial input power	144 W
Power consumption tolerance	+/-10%


Application Conditions

Ambient temperature range	-30 to +50 °C
---------------------------	---------------


Product Data

Full product code	871951451059300
Order product name	BY570P LED200/840 PSU WB CAU CL

EAN/UPC – product	8719514510593
Order code	911401596661
Numerator – quantity per pack	1
SAP numerator – packs per outer box	1
Material no. (12 NC)	911401596661
SAP net weight (piece)	3.599 kg



Dimensional drawing



High-bay/ low-bay LED

