



# UNIUrban

## BSS461 LED120 NW 230V SR CLASSIC 7P


UNIUrban is ideal for urban lighting across pathways, parks, gardens, residential areas and shopping centre areas. Its exquisite, stylish yet classic design is not only suitable for modern cities but also for historical architecture.

### Product data


General Information	
Lamp colour code	740 neutral white
Driver included	Yes
Optical cover/lens type	No [-]
Control interface	-
Connection	Flying leads/wires
Cable	Cable 0.5 m without plug
Protection class IEC	Safety class I (I)
CE mark	CE mark
Operating and Electrical	
Input Voltage	220 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.95
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum die-cast
Optical cover/lens material	Polycarbonate
Overall height	377 mm
Overall diameter	482 mm

Colour	Aluminium and Grey
Approval and Application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
Initial Performance (IEC Compliant)	
Initial luminous flux	12000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>70
Initial input power	100 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	911401756032
Order product name	BSS461 LED120 NW 230V SR CLASSIC 7P
Order code	911401756032
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1

Material no. (12 NC)	911401756032
Net Weight (Piece)	8.450 kg



## Dimensional drawing



UNIUrban BDP461/BGP461/BSP461/BSS461

