



ZXP399 DMX Controls and Accessories

SSLCTR ACTIVESITE GATEWAY

CE mark - UL mark

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up 100 metres.

Product data


General Information	
CE mark	CE mark
UL mark	UL mark
Mechanical and Housing	
Colour	Black
Dimensions (height x width x depth)	NaN x NaN x NaN mm (NaN x NaN x NaN in)

Initial Performance (IEC Compliant)	
Initial input power	40 W
Product Data	
Full product code	871829164576400
Order product name	SSLCTR ACTIVESITE GATEWAY
EAN/UPC – product	8718291645764
Order code	912400133649
Numerator – quantity per pack	1
SAP numerator – packs per outer box	1

ZXP399 DMX Controls and Accessories

Material no. (12 NC)	912400133649
SAP net weight (piece)	2.446 kg

Dimensional drawing



ZXP399

