



MASTER TL5 Circular

MASTER TL5 Circular 40W/840 1CT/10

16 mm tube diameter circular fluorescent lamps with a choice of various diameters

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	2GX13 [2GX13]
Life to 50% failures preheat (nom.)	12000 h
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	99 %
LSF preheat 6,000 hours rated	96 %
LSF preheat 8,000 hours rated	89 %
LSF preheat 16,000 hours rated	10 %
LSF preheat 20,000 hours rated	1 %

Light Technical	
Colour Code	840 [CCT of 4,000 K]
Lamp Luminous Flux 25°C EL (Nom)	3300 lm
Lamp Luminous Flux (Nom)	3300 lm
Colour Designation	Cool White (CW)
Colour Temperature, horizontal (Nom)	4000 K
Lamp Luminous Efficacy EM (Nom)	83 lm/W
Colour Rendering Index, horiz (Nom)	82
LLMF 2000 h Rated	91 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	84 %

LLMF 8000 h Rated	81 %
LLMF 12000 h Rated	77 %
LLMF 16000 h Rated	74 %
LLMF 20000 h Rated	72 %

Operating and Electrical	
Power (Rated) (Nom)	39.9 W
Lamp current (nom.)	0.320 A

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	4 mg
Energy consumption kWh/1,000 hours	44 kWh


Product Data	
Full product code	871150064223325
Order product name	MASTER TL5 Circular 40W/840 1CT/10
EAN/UPC – product	8711500642233

MASTER TL5 Circular

Order code	927965584013
Local code	TL5C40W840
Numerator – quantity per pack	1
SAP numerator – packs per outer box	10
Material no. (12 NC)	927965584013

Net Weight (Piece)	0.110 kg
ILCOS code	FSCH-40/40/1B-L/P-2GX13-16


Dimensional drawing




TL5-C 40W/840

Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 40W/840 1CT/10	18 mm	14 mm	293 mm	305 mm	260 mm	272 mm

Photometric data




Lightcolour /840




Lightcolour /840

Lifetime




LDLE_TL5-C8_0001-Life expectancy diagram



LDLE_TL5-C8_0002-Life expectancy diagram

MASTER TL5 Circular

Lifetime



LDLM_TL5-C8_0001-Lumen maintenance diagram

