



MSR

MSR 400 1CT/4

MSR – bright vivid colours, always The high colour rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colours of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap base	GX9.5 [GX9.5]	Lamp Luminous Efficacy EM (Nom)	79 lm/W
Burning Position	UNIVERSAL [Any/Universal]	Colour Rendering Index,horiz (Nom)	95
Main application	Studio/Disco	Power (Rated) (Nom)	400 W
Life to 50% failures (nom.)	1000 h	Lamp current (nom.)	7 A
System description	Cold Strike	Ignition supply voltage (min.)	207 V
Light Technical		Controls and Dimming	
Colour Code	- [Not Specified]	Dimmable	No
Lamp Luminous Flux 25°C EL (Min)	28440 lm	Mechanical and Housing	
Lamp Luminous Flux 25°C EL (Nom)	32000 lm	Cap-base information	na [-]
Chromaticity coordinate X (nom.)	325		
Chromaticity coordinate Y (nom.)	320		
Colour Temperature, horizontal (Nom)	5830 K		

MSR

Luminaire Design Requirements

Bulb temperature (max.)	700 °C
Pinch temperature (max.)	350 °C

Product Data

Full product code	871869641600600
Order product name	MSR 400 1CT/4
EAN/UPC – product	8718696416006

Order code	928077905115
Local order code	MSR400
SAP numerator – quantity per pack	1
SAP numerator – packs per outer box	4
Material no. (12 NC)	928077905115
SAP net weight (piece)	44.000 g

Dimensional drawing

0

Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 400	23 mm	6.0	61 mm	63 mm	62	112 mm	36 mm	35	34 mm
1CT/4		mm			mm			mm	

MSR 400

Photometric data

