



MSR Short Arc

MSR 700 SA 1CT/4

MSR Short Arc – for longer life The lamp’s short arc and compact design helps enable a compact luminaire that provides high beam intensity, while the excellent colour rendition characteristics help ensure optimal colours on stage. The highly innovative P3 technology, developed by Philips, allows MSR Short Arc lamps to be used at higher temperatures in any burning position. The result? Longer lifetime, fewer early failures and a highly consistent performance throughout the lamp’s lifetime.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Colour Rendering Index,horiz (Nom)	
Cap base	GY9.5 [GY9.5]		80
Burning Position	UNIVERSAL [Any/Universal]	Operating and Electrical	
Main application	Studio/Disco	Power (Rated) (Nom)	700 W
Life to 50% failures (nom.)	750 h	Lamp current (nom.)	11 A
System description	Short Arc	Ignition supply voltage (min.)	207 V
Light Technical		Controls and Dimming	
Colour Code	- [Not Specified]	Dimmable	No
Lamp Luminous Flux 25°C EL (Min)	49500 lm	Mechanical and Housing	
Lamp Luminous Flux 25°C EL (Nom)	55000 lm	Cap-base information	na [-]
Chromaticity coordinate X (nom.)	333	Luminaire Design Requirements	
Chromaticity coordinate Y (nom.)	342	Bulb temperature (max.)	1000 °C
Colour Temperature, horizontal (Nom)	5600 K		
Lamp Luminous Efficacy EM (Nom)	78 lm/W		

MSR Short Arc

Pinch temperature (max.)	500 °C
Product Data	
Full product code	871829122802800
Order product name	MSR 700 SA 1CT/4
EAN/UPC – product	8718291228028
Order code	928170305115

SAP numerator – quantity per pack	1
SAP numerator – packs per outer box	4
SAP material	928170305115
Net Weight (Piece)	0.020 kg


Dimensional drawing



MSR 700 SA

Product	D (max)	O	L (min)	L (max)	L	C (max)
MSR 700 SA 1CT/4	25 mm	4.0 mm	38 mm	40 mm	39 mm	83 mm

Photometric data



XDPB_XDMSR_SA-Spectral power distribution B/W

